


PROBLEM 3.64

KNOWN: Diameter of a spherical container used to store liquid oxygen and properties of insulating material. Environmental conditions.

FIND: (a) Reduction in evaporative oxygen loss associated with a prescribed insulation thickness, (b) Effect of insulation thickness on evaporation rate.

SCHEMATIC:



ASSUMPTIONS: (1) Steady-state, one-dimensional conduction, (2) Negligible conduction resistance of container wall and contact resistance between wall and insulation, (3) Container wall at boiling point of liquid oxygen.

ANALYSIS: (a) Applying an energy balance to a control surface about the insulation, $\dot{E}_{in} - \dot{E}_{out} = 0$, it follows that $q_{conv} + q_{rad} = q_{cond} = q$. Hence,

$$\frac{T_{\infty} - T_{s,2}}{R_{t,conv}} + \frac{T_{sur} - T_{s,2}}{R_{t,rad}} = \frac{T_{s,2} - T_{s,1}}{R_{t,cond}} = q \quad (1)$$

where $R_{t,conv} = (4\pi r_2^2 h)^{-1}$, $R_{t,rad} = (4\pi r_2^2 h_r)^{-1}$, $R_{t,cond} = (1/4\pi k)[(1/r_1) - (1/r_2)]$, and, from Eq.

1.9, the radiation coefficient is $h_r = \varepsilon \sigma (T_{s,2} + T_{sur})(T_{s,2}^2 + T_{sur}^2)$. With $t = 10$ mm ($r_2 = 260$ mm), $\varepsilon = 0.2$ and $T_{\infty} = T_{sur} = 298$ K, an iterative solution of the energy balance equation yields $T_{s,2} \approx 297.7$ K, where $R_{t,conv} = 0.118$ K/W, $R_{t,rad} = 0.982$ K/W and $R_{t,cond} = 76.5$ K/W. With the insulation, it follows that the heat gain is

$$q_w \approx 2.72 \text{ W}$$

Without the insulation, the heat gain is

$$q_{wo} = \frac{T_{\infty} - T_{s,1}}{R_{t,conv}} + \frac{T_{sur} - T_{s,1}}{R_{t,rad}}$$

where, with $r_2 = r_1$, $T_{s,1} = 90$ K, $R_{t,conv} = 0.127$ K/W and $R_{t,rad} = 3.14$ K/W. Hence,

$$q_{wo} = 1702 \text{ W}$$

With the oxygen mass evaporation rate given by $\dot{m} = q/h_{fg}$, the percent reduction in evaporated oxygen is

$$\% \text{ Reduction} = \frac{\dot{m}_{wo} - \dot{m}_w}{\dot{m}_{wo}} \times 100\% = \frac{q_{wo} - q_w}{q_{wo}} \times 100\%$$

Hence,


$$\% \text{ Reduction} = \frac{(1702 - 2.7) \text{ W}}{1702 \text{ W}} \times 100\% = 99.8\%$$

<

Continued...

PROBLEM 3.64 (Cont.)

(b) Using Equation (1) to compute $T_{s,2}$ and q as a function of r_2 , the corresponding evaporation rate, $\dot{m} = q/h_{fg}$, may be determined. Variations of q and \dot{m} with r_2 are plotted as follows.



Because of its extremely low thermal conductivity, significant benefits are associated with using even a thin layer of insulation. Nearly three-order magnitude reductions in q and \dot{m} are achieved with $r_2 = 0.26$ m. With increasing r_2 , q and \dot{m} decrease from values of 1702 W and 8×10^{-3} kg/s at $r_2 = 0.25$ m to 0.627 W and 2.9×10^{-6} kg/s at $r_2 = 0.30$ m.

COMMENTS: Laminated metallic-foil/glass-mat insulations are extremely effective and corresponding conduction resistances are typically much larger than those normally associated with surface convection and radiation.