


PROBLEM 5.44

KNOWN: One-dimensional wall, initially at a uniform temperature, T_i , is suddenly exposed to a convection process (T_∞, h). For wall #1, the time ($t_1 = 100\text{s}$) required to reach a specified temperature at $x = L$ is prescribed, $T(L_1, t_1) = 315^\circ\text{C}$.

FIND: For wall #2 of different thickness and thermal conditions, the time, t_2 , required for $T(L_2, t_2) = 28^\circ\text{C}$.

SCHEMATIC:



ASSUMPTIONS: (1) One-dimensional conduction, (2) Constant properties.

ANALYSIS: The properties, thickness and thermal conditions for the two walls are:

Wall	L(m)	$\alpha(\text{m}^2/\text{s})$	k(W/m·K)	$T_i(^{\circ}\text{C})$	$T_\infty(^{\circ}\text{C})$	h(W/m ² ·K)
1	0.10	15×10^{-6}	50	300	400	200
2	0.40	25×10^{-6}	100	30	20	100

The dimensionless functional dependence for the one-dimensional, transient temperature distribution, Eq. 5.38, is

$$\theta^* = \frac{T(x,t) - T_\infty}{T_i - T_\infty} = f(x^*, \text{Bi}, \text{Fo})$$

where

$$x^* = x/L \quad \text{Bi} = hL/k \quad \text{Fo} = \alpha t/L^2.$$

If the parameters x^* , Bi, and Fo are the same for both walls, then $\theta_1^* = \theta_2^*$. Evaluate these parameters:

Wall	x^*	Bi	Fo	θ^*
1	1	0.40	0.150	0.85
2	1	0.40	$1.563 \times 10^{-4} t_2$	0.85

where

$$\theta_1^* = \frac{315 - 400}{300 - 400} = 0.85 \quad \theta_2^* = \frac{28.5 - 20}{30 - 20} = 0.85.$$

It follows that

$$\text{Fo}_2 = \text{Fo}_1 \quad 1.563 \times 10^{-4} t_2 = 0.150$$

$$t_2 = 960\text{s}.$$

<