


### PROBLEM 3.84

**KNOWN:** Composite wall with outer surfaces exposed to convection process.

**FIND:** (a) Volumetric heat generation and thermal conductivity for material B required for special conditions, (b) Plot of temperature distribution, (c)  $T_1$  and  $T_2$ , as well as temperature distributions corresponding to loss of coolant condition where  $h = 0$  on surface A.

**SCHEMATIC:**




**ASSUMPTIONS:** (1) Steady-state, one-dimensional heat transfer, (2) Negligible contact resistance at interfaces, (3) Uniform generation in B; zero in A and C.

**ANALYSIS:** (a) From an energy balance on wall B,



$$\dot{E}_{in} - \dot{E}_{out} + \dot{E}_g = \dot{E}_{st}$$

$$-q_1'' - q_2'' + 2\dot{q}L_B = 0$$

$$\dot{q}_B = (q_1'' + q_2'')/2L_B \quad (1)$$



To determine the heat fluxes,  $q_1''$  and  $q_2''$ , construct thermal circuits for A and C:



$$q_1'' = (T_1 - T_\infty)/(1/h + L_A/k_A)$$

$$q_2'' = (T_2 - T_\infty)/(L_C/k_C + 1/h)$$

$$q_1'' = (261 - 25)^\circ\text{C} / \left( \frac{1}{1000 \text{ W/m}^2 \cdot \text{K}} + \frac{0.030 \text{ m}}{25 \text{ W/m} \cdot \text{K}} \right)$$

$$q_2'' = (211 - 25)^\circ\text{C} / \left( \frac{0.020 \text{ m}}{50 \text{ W/m} \cdot \text{K}} + \frac{1}{1000 \text{ W/m}^2 \cdot \text{K}} \right)$$

$$q_1'' = 236^\circ\text{C} / (0.001 + 0.0012) \text{ m}^2 \cdot \text{K/W}$$

$$q_2'' = 186^\circ\text{C} / (0.0004 + 0.001) \text{ m}^2 \cdot \text{K/W}$$

$$q_1'' = 107,273 \text{ W/m}^2$$

$$q_2'' = 132,857 \text{ W/m}^2$$

Using the values for  $q_1''$  and  $q_2''$  in Eq. (1), find

$$\dot{q}_B = (106,818 + 132,143 \text{ W/m}^2) / (2 \times 0.030 \text{ m}) = 4.00 \times 10^6 \text{ W/m}^3.$$

<

To determine  $k_B$ , use the general form of the temperature (Eq. 3.40) and heat flux distributions in wall B,

$$T(x) = -\frac{\dot{q}_B}{2k_B}x^2 + C_1x + C_2 \quad q_x''(x) = -k_B \left[ -\frac{\dot{q}_B}{k_B}x + C_1 \right] \quad (2,3)$$

there are 3 unknowns,  $C_1$ ,  $C_2$  and  $k_B$ , which can be evaluated using three conditions,

Continued...

### PROBLEM 3.84 (Cont.)

$$T(-L_B) = T_1 = -\frac{\dot{q}_B}{2k_B}(-L_B)^2 - C_1L_B + C_2 \quad \text{where } T_1 = 261^\circ\text{C} \quad (4)$$

$$T(+L_B) = T_2 = -\frac{\dot{q}_B}{2k_B}(+L_B)^2 + C_1L_B + C_2 \quad \text{where } T_2 = 211^\circ\text{C} \quad (5)$$

$$q_x''(-L_B) = -q_1'' = -k_B \left[ -\frac{\dot{q}_B}{k_B}(-L_B) + C_1 \right] \quad \text{where } q_1'' = 107,273 \text{ W/m}^2 \quad (6)$$

Using IHT to solve Eqs. (4), (5) and (6) simultaneously with  $\dot{q}_B = 4.00 \times 10^6 \text{ W/m}^3$ , find

$$k_B = 15.3 \text{ W/m} \cdot \text{K}$$

(b) Following the method of analysis in the *IHT Example 3.6, User-Defined Functions*, the temperature distribution is shown in the plot below. The important features are (1) Distribution is quadratic in B, but non-symmetrical; linear in A and C; (2) Because thermal conductivities of the materials are different, discontinuities exist at each interface; (3) By comparison of gradients at  $x = -L_B$  and  $+L_B$ , find  $q_2'' > q_1''$ .

(c) Using the same method of analysis as for Part (c), the temperature distribution is shown in the plot below when  $h = 0$  on the surface of A. Since the left boundary is adiabatic, material A will be isothermal at  $T_1$ . Find

$$T_1 = 835^\circ\text{C}$$

$$T_2 = 360^\circ\text{C}$$

