


PROBLEM 6S.2

KNOWN: Oil properties, journal and bearing temperatures, and journal speed for a lightly loaded journal bearing.

FIND: Maximum oil temperature.

SCHEMATIC:



ASSUMPTIONS: (1) Steady-state conditions, (2) Incompressible fluid with constant properties, (3) Clearance is much less than journal radius and flow is Couette.

ANALYSIS: The temperature distribution corresponds to the result obtained in the text Example on Couette flow,

$$T(y) = T_0 + \frac{\mu}{2k} U^2 \left[\frac{y}{L} - \left[\frac{y}{L} \right]^2 \right].$$

The position of maximum temperature is obtained from

$$\frac{dT}{dy} = 0 = \frac{\mu}{2k} U^2 \left[\frac{1}{L} - \frac{2y}{L^2} \right]$$

or, $y = L/2$.

The temperature is a maximum at this point since $d^2T/dy^2 < 0$. Hence,

$$T_{\max} = T(L/2) = T_0 + \frac{\mu}{2k} U^2 \left[\frac{1}{2} - \frac{1}{4} \right] = T_0 + \frac{\mu U^2}{8k}$$

$$T_{\max} = 40^\circ\text{C} + \frac{10^{-2} \text{ kg/s} \cdot \text{m} (10 \text{ m/s})^2}{8 \times 0.15 \text{ W/m} \cdot \text{K}}$$

$$T_{\max} = 40.83^\circ\text{C}.$$

<

COMMENTS: Note that T_{\max} *increases* with *increasing* μ and U , *decreases* with *increasing* k , and is *independent* of L .